

ISSUE 10; September 2019

Description

- Standard 3.2 x 2.5mm SMD crystal in a ceramic package with a seam sealed metal lid, hermetically sealed.

Frequency Parameters

- Frequency 10.0MHz to 200.0MHz
- Frequency Tolerance $\pm 10.00\text{ppm}$ to $\pm 50.00\text{ppm}$
- Tolerance Condition @ 25°C
- Frequency Stability $\pm 10.00\text{ppm}$ to $\pm 50.00\text{ppm}$
- Ageing $\pm 5\text{ppm}$ max per year @ 25°C

Electrical Parameters

- Load Capacitance (CL) 4.0pF to 75.0pF
- Shunt Capacitance (C0) 7pF max
- Drive Level 100µW max

Operating Temperature Ranges

- 10 to 60°C
- 10 to 70°C
- 20 to 70°C
- 40 to 85°C

Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Shock: MIL-STD-202F, Method 213B: 1000G, 0.5ms, 1/2 sine wave
- Vibration: MIL-STD-202F, Method 204D, Test Condition D: 20G (10Hz-2000Hz), 4hrs in 3 mutually perpendicular planes (total 12hrs)

Manufacturing Details

- RoHS Terminations NiAu
- RoHS Reflow 260degC 10s

Ordering Information


- Frequency*
- Model*
- Frequency Tolerance*
- Frequency Stability (over operating temperature range)*
- Operating Temperature Range*
- Load Capacitance*
- Overtone (*minimum required)
- Example
20.0MHz CFPX-180
50/50/-40 to 85C/16 FUND

Compliance


- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JEDEC-STD-033): Not Applicable

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
Pack Size: 1,000
- Pack Style: Cutt In tape, cut from a reel
Pack Size: 100



Outline (mm)



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Electrical Specification - maximum limiting values

Frequency Min	Frequency Max	Temperature Range	Stability Min*	Over Tone Order	ESR
		°C	ppm		Ω
10.0MHz	11.999999MHz	-10 to 70 -20 to 70 -40 to 85	±10 ±10 ±15	Fundamental	200
12.0MHz	15.999999MHz	-10 to 70 -20 to 70 -40 to 85	±10 ±10 ±15	Fundamental	120
16.0MHz	19.999999MHz	-10 to 70 -20 to 70 -40 to 85	±10 ±10 ±15	Fundamental	70
20.0MHz	29.999999MHz	-10 to 60 -20 to 70 -40 to 85	±10 ±10 ±15	Fundamental	50
30.0MHz	39.999999MHz	-10 to 70 -20 to 70 -40 to 85	±10 ±10 ±15	Fundamental	40
40.0MHz	54.0MHz	-10 to 60 -20 to 70 -40 to 85	±10 ±10 ±15	Fundamental	35
54.000001MHz	200.0MHz	-10 to 70 -20 to 70 -40 to 85	±30 ±30 ±30	Fundamental	60

*Stability Maximum values ±50ppm

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com