

ISSUE 2; June 2019

### Description

- This product is designed and manufactured by Statek Corporation in California, USA and distributed by IQD. Statek's high shock HFXO oscillators, available in tight frequency tolerances, consist of a Statek miniature quartz crystal and a CMOS/TTL compatible hybrid circuit in a ceramic package. Each crystal used in the HFXO oscillator is pre-qualified before assembly through electrical tests and characterisation over temperature.
- A-SM1 5000G, Gold Plated (lead free)
- A-SM5 5000G, Solder Dipped (lead free)
- B-SM1 10000G, Gold Plated (lead free)
- B-SM5 10000G, Solder Dipped (lead free)
- C-SM1 20000G, Gold Plated (lead free)
- C-SM5 20000G, Solder Dipped (lead free)
- D-SM1 30000G, Gold Plated (lead free)
- D-SM5 30000G, Solder Dipped (lead free)
- F-SM1 50000G, Gold Plated (lead free)
- F-SM5 50000G, Solder Dipped (lead free)
- G-SM1 75000G, Gold Plated (lead free)
- G-SM5 75000G, Solder Dipped (lead free)
- Please note that all data is only valid at 25°C unless otherwise stated.

### Frequency Parameters

- |                     |                         |
|---------------------|-------------------------|
| Frequency           | 220.0kHz to 100.0MHz    |
| Frequency Tolerance | ±10.00ppm to ±100.00ppm |
| Tolerance Condition | @ 25°C                  |
| Frequency Stability | ±10.00ppm to ±100.00ppm |
| Ageing              | ±5ppm max in 1st year   |

### Electrical Parameters

- Supply Voltage 1.8V ±5%
- Absolute Maximum Supply Voltage: -0.5V to 7.0V  
Note: the supply voltage range is -0.5V to 4.0V for some products.

### Operating Temperature Ranges

- 10 to 70°C
- 40 to 85°C
- 55 to 125°C

### Output Details

- Output Compatibility CMOS
- Drive Capability 15pF




### Environmental Parameters

- Shock: 0.5ms, 1/2 sine up to 75000G
- Vibration: 20G, 10Hz-2000Hz, swept sine
- Storage Temperature Range: -55 to 125°C

### Manufacturing Details


- Maximum Process Temperature: 260°C for 20 seconds max

Outline (mm) -A-SM1 = 5000G, Gold Plated (lead free)



Pad Connections	Height (H) =
1. EN/TS/NC	SM1 1.73mm max
2. GND	SM3 1.91mm max
3. Output	SM5 1.91mm max
4. +Vs	

Solder Pad Layout



### Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1 760 318 2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)

Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

**Ordering Information**

- Minimum required\*
  - Frequency\*
  - Model\*
  - Termination Variant\*
  - Output Compatibility
  - Frequency Tolerance (@25°C)\*
  - Frequency Stability (over operating temperature range)\*
  - Operating Temperature Range\*
  - Pad 1 Function\*
  - Shock Requirement\*
- Example
  - 40.0MHz HFXO 1.8V-A-SM1
  - CMOS ±10ppm ±20ppm -10 to 70C NC
- Shock Level Options:
  - A = 5000G
  - B = 10000G
  - C = 20000G
  - D = 30000G
  - F = 50000G
  - G = 75000G
- Termination Options:
  - SM1 = Gold Plated
  - SM3 = Solder Dipped (non RoHS)
  - SM5 = Solder Dipped (Pb free)

**Compliance**

- RoHS Status (2015/863/EU)      Optional
- REACH Status                      Compliant
- MSL Rating (JDEC-STD-033):    Not Applicable

**Packaging Details**

- Pack Style: Tray      Supplied on a tray  
Pack Size: 1
- Pack Style: Reel      Tape & reel in accordance with EIA-481-D  
Pack Size: 1,000

**Electrical Specification - maximum limiting values 1.8V ±5%**

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
220.0kHz	100.0MHz	-10 to 70	±10.0	-	10	40/60%
		-40 to 85	±20.0	-	10	40/60%
		-55 to 125	±40.0	-	10	40/60%

*This document was correct at the time of printing; please contact your local sales office for the latest version.*  
[Click to view latest version on our website.](#)

**Sales Office Contact Details:**

UK: +44 (0)1460 270200

USA: +1 760 318 2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)

Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)