

ISSUE 2; March 2022



Description

- PLL based, one time only factory programmable for a fast lead time crystal oscillator in a hermetically sealed ceramic package with a metal lid. This model has extra testing performed during manufacture specifically for Aviation customers buying this standard commercial product.
- -A A = Enable/Disable
- -B B = Power-Down

Frequency Parameters

- Frequency 1.0MHz to 200.0MHz
- Frequency Stability $\pm 15.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing $\pm 3\text{ppm}$ max in 1st year @ 25°C

Electrical Parameters

- Supply Voltage 3.3V $\pm 5\%$

Operating Temperature Ranges

- -20 to 70°C
- -40 to 85°C
- -40 to 105°C

Output Details

- Output Compatibility CMOS
- Drive Capability 15pF max
- Start Up Time: 5ms max.
In Power-Down mode, the internal oscillator shuts down and the start-up time will be longer compared to Enable/Disable mode.
- Logic '1' (>70% Vs) to pad 1 enables oscillator output
Logic '0' (<30% Vs) to pad 1 disables oscillator output; when disabled the oscillator output goes to the high impedance state
No connection to pad 1 enables oscillator output

Output Control

- Standby Current (Enable/Disable): 20mA max
- Standby Current (Power-Down): 400µA max

Noise Parameters


- RMS Phase Jitter (12KHz to 20MHz) @ 3.3V: 1ps max

Environmental Parameters


- Storage Temperature Range: -55 to 125°C

Manufacturing Details

- Additional:
 - 1) Sample AQL reflow profile test.
 - 2) 100% frequency and output voltage test.
 - 3) Sample AQL electrical test over operating temperature range.
- RoHS Terminations Au
- RoHS Reflow 260°C 10s max




Outline (mm) -A = A = Enable/Disable



Pad Connections

1. Enable/Disable
2. GND
3. Output
4. Vs

Outline (mm) -B = B = Power-Down



Pad Connections

1. Power-Down
2. GND
3. Output
4. Vs

Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com

Ordering Information

- Frequency*
 Model*
 -A = Enable/Disable or -B = Power-Down
 Output Compatibility
 Frequency Stability (over operating temperature range)*
 Operating Temperature Range*
 Supply Voltage
- Example
 20.0MHz IQPP-73 Aviation-A
 CMOS ± 50 ppm -40 to 85°C 3.3V


Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details


- Pack Style: Reel Tape & reel in accordance with EIA-481-D
 Pack Size: 1,000
- Pack Style: Cutt In tape, cut from a reel
 Pack Size: 100

Solder Pad Layout




To ensure optimal oscillator performance, place a by-pass capacitor of 0.1µF as close to the part as possible between Vdd & GND pads

Wave Form



Test Circuit



Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com

Electrical Specification - maximum limiting values 3.3V \pm 5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
1.0MHz	200.0MHz	-20 to 70	\pm 15.0	35	2	45/55%
		-40 to 85	\pm 25.0	35	2	45/55%
		-40 to 105	\pm 50.0	35	2	45/55%

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com