

ISSUE 4; April 2021

Description

- Low EMI Spread Spectrum surface mount crystal oscillator in a ceramic package hermetically sealed with a seam sealed metal lid
- ±0.125% Centre Spread
- ±0.25% Centre Spread
- ±0.5% Centre Spread
- ±1% Centre Spread
- ±1.5% Centre Spread
- ±2% Centre Spread
- 0.25% Down Spread
- 0.5% Down Spread
- 1% Down Spread
- 2% Down Spread
- 4% Down Spread

Frequency Parameters

- Frequency: 1.0MHz to 200.0MHz
- Frequency Stability: ±25.00ppm to ±100.00ppm
- Ageing: ±3ppm max per year @ 25°C

Electrical Parameters

- Supply Voltage: 3.3V ±10%
- Internal Spread Spectrum Modulation Frequency: 30kHz to 40kHz

Operating Temperature Ranges

- 10 to 70°C
- 40 to 85°C

Output Details

- Output Compatibility: CMOS
- Drive Capability: 15pF max
- Standby Current: 10µA max
- Modulation Ratios:
 - Centre Spread ±0.125%, ±0.25%, ±0.5%, ±1%, ±2%
 - Down Spread -0.25%, -0.5%, -1%, -2%, -4%

Output Control

- Standby Operation:
 - Logic '1' to pad 1 enables oscillator output
 - Logic '0' to pad 1 disables oscillator output, the oscillator output goes to a high impedance state
 - No connection to pad 1 enables oscillator output



Noise Parameters

- Cycle to Cycle Jitter (1-σ): 100ps max


Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Shock: 1500G, 0.5ms, 3 times in each of 3 mutually perpendicular planes
- Vibration: 20G, 20-2000Hz, 1.52mm amplitude, 4 cycles of 20mins in 3 mutually perpendicular planes (total 4hrs)


Outline (mm) ±0.125% = Centre Spread



- Pad Connections
- Standby Operation
 - GND
 - Output
 - +Vs




Test Circuit



* Inclusive of jigging and equipment capacitance

Example Output Spectrum (Centre Spread ±1%)



Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com

Manufacturing Details

- RoHS Terminations Au over Ni over W base
- RoHS Reflow 260°C for 10secs max

Ordering Information

- Frequency*
- Model*
- Modulation Ratio*
- Output
- Frequency Stability (over operating temperature range)*
- Operating Temperature Range*
- Supply Voltage
- (*minimum required)
- Example
- 20.0MHz IQXS-10 ±1%
- CMOS ±50ppm -10 to 70C 3.3V

Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
- Pack Size: 1,000
- Pack Style: Cutt Cutt from Tape & Reel
- Pack Size: 1

Electrical Specification - maximum limiting values 3.3V ±10%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
1.0MHz	49.999999MHz	-10 to 70	±25.0	20	10	40/60%
		-40 to 85	±25.0	20	10	40/60%
50.0MHz	99.999999MHz	-10 to 70	±25.0	30	5	40/60%
		-40 to 85	±25.0	30	5	40/60%
100.0MHz	149.999999MHz	-10 to 70	±25.0	35	4	40/60%
		-40 to 85	±25.0	35	4	40/60%
150.0MHz	200.0MHz	-10 to 70	±25.0	40	3	40/60%
		-40 to 85	±25.0	40	3	40/60%

This document was correct at the time of printing; please contact your local sales office for the latest version.
[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com