



## IQXT-205-1

IQXT-205-1

IQXT-205-1 is a 2.0 x 1.6mm SMD Temperature Compensated Crystal Oscillator (TCXO) in a hermetically sealed package.

Model Name	Description
IQXT-205-1-18	A 1.8V version
IQXT-205-1-25	A 2.5V version
IQXT-205-1-28	A 2.8V version
IQXT-205-1-30	A 3.0V version
IQXT-205-1-33	A 3.3V version

ISSUE 1; November 2020

### Description

- IQXT-205-1-18 is a 2.0 x 1.6mm SMD Temperature Compensated Crystal Oscillator (TCXO) in a hermetically sealed package.
- Developed frequencies: 16.2, 16.368, 16.369, 19.2, 20.0, 24.0, 25.0, 26.0, 27.456, 28.925, 28.974, 30.0, 32.0, 33.6, 38.4, 48.0, 50.0 and 52.0MHz



### Frequency Parameters

- Frequency 13.0MHz to 52.0MHz
- Frequency Tolerance Max  $\pm 1.50\text{ppm}$
- Tolerance Condition @ 25°C  $\pm 2^\circ\text{C}$
- Frequency Stability  $\pm 0.50\text{ppm}$
- Ageing  $\pm 1\text{ppm}$  max per year @ 25°C  $\pm 3^\circ\text{C}$
- Frequency Tolerance: Referred to nominal frequency before reflow soldering.
- Supply Voltage Variation (@  $\pm 5\%$  change):  $\pm 0.1\text{ppm}$  max
- Load Variation (@  $\pm 10\%$  change):  $\pm 0.1\text{ppm}$  max
- Short Term Stability (Allan variance):  $\pm 1\text{ppb}$  max (Tau = 0.1s)
- IR Reflow Resistance (ref to frequency before reflow):  $\pm 1\text{ppm}$  max

### Electrical Parameters

- Supply Voltage 1.8V  $\pm 5\%$
- Absolute Maximum Ratings: Supply Voltage: -0.6V to 4.6V

### Operating Temperature Ranges

- -30 to 85°C

### Output Details

- Output Compatibility Clipped Sine
- Drive Capability 10k $\Omega$ /10pF
- Output: DC coupled
- Output Level: 0.8V pk-pk min
- Start Up Time (90% of V pk-pk): 2ms max
- Start Up Time (within  $\pm 0.5\text{ppm}$ ): 2ms max

### Noise Parameters

- Phase Noise (typ): -135dBc/Hz @ 1kHz
- Harmonic Distortion: -5.0dBc max

### Environmental Parameters


- Storage Temperature Range: -40 to 85°C

### Ordering Information


- \*Minimum info required  
Frequency\*  
Model\*  
Output  
Frequency Stability (over operating temperature range)\*  
Operating Temperature Range\*  
Supply Voltage
- Example  
20.0MHz IQXT-205-1-18  
Clipped Sine  $\pm 0.5\text{ppm}$  -30 to 85C 1.8V

### Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable



### Outline (mm)



#### Pad Connections

1. GND
2. GND
3. Output
4. +Vs

#### Solder Pad Layout



ISSUE 1; November 2020

#### Packaging Details

- Pack Style: Reel      Tape & reel in accordance with EIA-481  
Pack Size: 3,000

Electrical Specification - maximum limiting values 1.8V  $\pm$ 5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
13.0MHz	29.999999MHz	-30 to 85	$\pm$ 0.5	1.5	-	-
30.0MHz	39.999999MHz	-30 to 85	$\pm$ 0.5	1.7	-	-
40.0MHz	52.0MHz	-30 to 85	$\pm$ 0.5	2	-	-

*This document was correct at the time of printing; please contact your local sales office for the latest version.*

[Click to view latest version on our website.](#)

ISSUE 1; November 2020

### Description

- IQXT-205-1-25 is a 2.0 x 1.6mm SMD Temperature Compensated Crystal Oscillator (TCXO) in a hermetically sealed package.
- Developed frequencies: 16.2, 16.368, 16.369, 19.2, 20.0, 24.0, 25.0, 26.0, 27.456, 28.925, 28.974, 30.0, 32.0, 33.6, 38.4, 48.0, 50.0 and 52.0MHz

### Frequency Parameters

- Frequency 13.0MHz to 52.0MHz
- Frequency Tolerance Max  $\pm 1.50\text{ppm}$
- Tolerance Condition @ 25°C  $\pm 2^\circ\text{C}$
- Frequency Stability  $\pm 0.50\text{ppm}$
- Ageing  $\pm 1\text{ppm}$  max per year @ 25°C  $\pm 3^\circ\text{C}$
- Frequency Tolerance: Referred to nominal frequency before reflow soldering.
- Supply Voltage Variation (@  $\pm 5\%$  change):  $\pm 0.1\text{ppm}$  max
- Load Variation (@  $\pm 10\%$  change):  $\pm 0.1\text{ppm}$  max
- Short Term Stability (Allan variance):  $\pm 1\text{ppb}$  max (Tau = 0.1s)
- IR Reflow Resistance (ref to frequency before reflow):  $\pm 1\text{ppm}$  max

### Electrical Parameters

- Supply Voltage 2.5V  $\pm 5\%$
- Absolute Maximum Ratings: Supply Voltage: -0.6V to 4.6V

### Operating Temperature Ranges

- -30 to 85°C

### Output Details

- Output Compatibility Clipped Sine
- Drive Capability 10k $\Omega$ /10pF
- Output: DC coupled
- Output Level: 0.8V pk-pk min
- Start Up Time (90% of V pk-pk): 2ms max
- Start Up Time (within  $\pm 0.5\text{ppm}$ ): 2ms max

### Noise Parameters

- Phase Noise (typ): -135dBc/Hz @ 1kHz
- Harmonic Distortion: -5.0dBc max

### Environmental Parameters


- Storage Temperature Range: -40 to 85°C

### Ordering Information


- \*Minimum info required  
Frequency\*  
Model\*  
Output  
Frequency Stability (over operating temperature range)\*  
Operating Temperature Range\*  
Supply Voltage
- Example  
20.0MHz IQXT-205-1-25  
Clipped Sine  $\pm 0.5\text{ppm}$  -30 to 85C 2.5V

### Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable



### Outline (mm)





ISSUE 1; November 2020

#### Packaging Details

- Pack Style: Reel      Tape & reel in accordance with EIA-481  
Pack Size: 3,000

Electrical Specification - maximum limiting values 2.5V  $\pm$ 5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
13.0MHz	29.999999MHz	-30 to 85	$\pm$ 0.5	1.5	-	-
30.0MHz	39.999999MHz	-30 to 85	$\pm$ 0.5	1.7	-	-
40.0MHz	52.0MHz	-30 to 85	$\pm$ 0.5	2	-	-

*This document was correct at the time of printing; please contact your local sales office for the latest version.*

[Click to view latest version on our website.](#)

ISSUE 1; September 2023

### Description

- IQXT-205-1-28 is a 2.0 x 1.6mm SMD Temperature Compensated Crystal Oscillator (TCXO) in a hermetically sealed package.
- Developed frequencies: 16.2, 16.368, 16.369, 19.2, 20.0, 24.0, 25.0, 26.0, 27.456, 28.925, 28.974, 30.0, 32.0, 33.6, 38.4, 48.0, 50.0 and 52.0MHz



### Frequency Parameters

- Frequency 13.0MHz to 52.0MHz
- Frequency Tolerance Max  $\pm 1.50\text{ppm}$
- Tolerance Condition @ 25°C  $\pm 2^\circ\text{C}$
- Frequency Stability  $\pm 0.50\text{ppm}$
- Ageing  $\pm 1\text{ppm}$  max per year @ 25°C  $\pm 3^\circ\text{C}$
- Frequency Tolerance: Referred to nominal frequency before reflow soldering.
- Supply Voltage Variation (@  $\pm 5\%$  change):  $\pm 0.1\text{ppm}$  max
- Load Variation (@  $\pm 10\%$  change):  $\pm 0.1\text{ppm}$  max
- Short Term Stability (Allan variance):  $\pm 1\text{ppb}$  max (Tau = 0.1s)
- IR Reflow Resistance (ref to frequency before reflow):  $\pm 1\text{ppm}$  max

### Electrical Parameters

- Supply Voltage 2.8V  $\pm 5\%$
- Absolute Maximum Ratings: Supply Voltage: -0.6V to 4.6V

### Operating Temperature Ranges

- -30 to 85°C

### Output Details

- Output Compatibility Clipped Sine
- Drive Capability 10k $\Omega$ /10pF
- Output: DC coupled
- Output Level: 0.8V pk-pk min
- Start Up Time (90% of V pk-pk): 2ms max
- Start Up Time (within  $\pm 0.5\text{ppm}$ ): 2ms max

### Noise Parameters

- Phase Noise (typ): -135dBc/Hz @ 1kHz
- Harmonic Distortion: -5.0dBc max

### Environmental Parameters


- Storage Temperature Range: -40 to 85°C

### Ordering Information


- \*Minimum info required  
Frequency\*  
Model\*  
Output  
Frequency Stability (over operating temperature range)\*  
Operating Temperature Range\*  
Supply Voltage
- Example  
20.0MHz IQXT-205-1-28  
Clipped Sine  $\pm 0.5\text{ppm}$  -30 to 85C 2.8V

### Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable



### Outline (mm)



#### Pad Connections

1. GND
2. GND
3. Output
4. +Vs

#### Solder Pad Layout



ISSUE 1; September 2023

Packaging Details

- Pack Style: Reel      Tape & reel in accordance with EIA-481  
Pack Size: 3,000

Electrical Specification - maximum limiting values 2.8V ±5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
13.0MHz	29.999999MHz	-30 to 85	±0.5	1.5	-	-
30.0MHz	39.999999MHz	-30 to 85	±0.5	1.7	-	-
40.0MHz	52.0MHz	-30 to 85	±0.5	2	-	-

*This document was correct at the time of printing; please contact your local sales office for the latest version.*  
[Click to view latest version on our website.](#)

ISSUE 1; November 2020

### Description

- IQXT-205-1-30 is a 2.0 x 1.6mm SMD Temperature Compensated Crystal Oscillator (TCXO) in a hermetically sealed package.
- Developed frequencies: 16.2, 16.368, 16.369, 19.2, 20.0, 24.0, 25.0, 26.0, 27.456, 28.925, 28.974, 30.0, 32.0, 33.6, 38.4, 48.0, 50.0 and 52.0MHz



### Frequency Parameters

- Frequency 13.0MHz to 52.0MHz
- Frequency Tolerance Max  $\pm 1.50\text{ppm}$
- Tolerance Condition @ 25°C  $\pm 2^\circ\text{C}$
- Frequency Stability  $\pm 0.50\text{ppm}$
- Ageing  $\pm 1\text{ppm}$  max per year @ 25°C  $\pm 3^\circ\text{C}$
- Frequency Tolerance: Referred to nominal frequency before reflow soldering.
- Supply Voltage Variation (@  $\pm 5\%$  change):  $\pm 0.1\text{ppm}$  max
- Load Variation (@  $\pm 10\%$  change):  $\pm 0.1\text{ppm}$  max
- Short Term Stability (Allan variance):  $\pm 1\text{ppb}$  max (Tau = 0.1s)
- IR Reflow Resistance (ref to frequency before reflow):  $\pm 1\text{ppm}$  max

### Electrical Parameters

- Supply Voltage 3.0V  $\pm 5\%$
- Absolute Maximum Ratings: Supply Voltage: -0.6V to 4.6V

### Operating Temperature Ranges

- -30 to 85°C

### Output Details

- Output Compatibility Clipped Sine
- Drive Capability 10k $\Omega$ /10pF
- Output: DC coupled
- Output Level: 0.8V pk-pk min
- Start Up Time (90% of V pk-pk): 2ms max
- Start Up Time (within  $\pm 0.5\text{ppm}$ ): 2ms max

### Noise Parameters

- Phase Noise (typ): -135dBc/Hz @ 1kHz
- Harmonic Distortion: -5.0dBc max

### Environmental Parameters


- Storage Temperature Range: -40 to 85°C

### Ordering Information


- \*Minimum info required  
Frequency\*  
Model\*  
Output  
Frequency Stability (over operating temperature range)\*  
Operating Temperature Range\*  
Supply Voltage
- Example  
20.0MHz IQXT-205-1-30  
Clipped Sine  $\pm 0.5\text{ppm}$  -30 to 85C 3.0V

### Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable



### Outline (mm)







ISSUE 1; November 2020

**Packaging Details**

- Pack Style: Reel      Tape & reel in accordance with EIA-481  
Pack Size: 3,000

**Electrical Specification - maximum limiting values 3.0V  $\pm$ 5%**

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
13.0MHz	29.999999MHz	-30 to 85	$\pm$ 0.5	1.5	-	-
30.0MHz	39.999999MHz	-30 to 85	$\pm$ 0.5	1.7	-	-
40.0MHz	52.0MHz	-30 to 85	$\pm$ 0.5	2	-	-

*This document was correct at the time of printing; please contact your local sales office for the latest version.*

[Click to view latest version on our website.](#)

ISSUE 1; November 2020

### Description

- IQXT-205-1-33 is a 2.0 x 1.6mm SMD Temperature Compensated Crystal Oscillator (TCXO) in a hermetically sealed package.
- Developed frequencies: 16.2, 16.368, 16.369, 19.2, 20.0, 24.0, 25.0, 26.0, 27.456, 28.925, 28.974, 30.0, 32.0, 33.6, 38.4, 48.0, 50.0 and 52.0MHz



### Frequency Parameters

- Frequency 13.0MHz to 52.0MHz
- Frequency Tolerance Max  $\pm 1.50\text{ppm}$
- Tolerance Condition @  $25^{\circ}\text{C} \pm 2^{\circ}\text{C}$
- Frequency Stability  $\pm 0.50\text{ppm}$
- Ageing  $\pm 1\text{ppm}$  max per year @  $25^{\circ}\text{C} \pm 3^{\circ}\text{C}$
- Frequency Tolerance: Referred to nominal frequency before reflow soldering.
- Supply Voltage Variation (@  $\pm 5\%$  change):  $\pm 0.1\text{ppm}$  max
- Load Variation (@  $\pm 10\%$  change):  $\pm 0.1\text{ppm}$  max
- Short Term Stability (Allan variance):  $\pm 1\text{ppb}$  max (Tau = 0.1s)
- IR Reflow Resistance (ref to frequency before reflow):  $\pm 1\text{ppm}$  max

### Electrical Parameters

- Supply Voltage  $3.3\text{V} \pm 5\%$
- Absolute Maximum Ratings: Supply Voltage: -0.6V to 4.6V

### Operating Temperature Ranges

- -30 to  $85^{\circ}\text{C}$

### Output Details

- Output Compatibility Clipped Sine
- Drive Capability  $10\text{k}\Omega / 10\text{pF}$
- Output: DC coupled
- Output Level: 0.8V pk-pk min
- Start Up Time (90% of V pk-pk): 2ms max
- Start Up Time (within  $\pm 0.5\text{ppm}$ ): 2ms max

### Noise Parameters

- Phase Noise (typ): -135dBc/Hz @ 1kHz
- Harmonic Distortion: -5.0dBc max

### Environmental Parameters


- Storage Temperature Range: -40 to  $85^{\circ}\text{C}$

### Ordering Information


- \*Minimum info required  
Frequency\*  
Model\*  
Output  
Frequency Stability (over operating temperature range)\*  
Operating Temperature Range\*  
Supply Voltage
- Example  
20.0MHz IQXT-205-1-33  
Clipped Sine  $\pm 0.5\text{ppm}$  -30 to  $85^{\circ}\text{C}$  3.3V

### Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable



### Outline (mm)



#### Pad Connections

1. GND
2. GND
3. Output
4. +Vs

#### Solder Pad Layout

ISSUE 1; November 2020

#### Packaging Details

- Pack Style: Reel      Tape & reel in accordance with EIA-481  
     Pack Size: 3,000

Electrical Specification - maximum limiting values 3.3V  $\pm$ 5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
13.0MHz	29.999999MHz	-30 to 85	$\pm$ 0.5	1.5	-	-
30.0MHz	39.999999MHz	-30 to 85	$\pm$ 0.5	1.7	-	-
40.0MHz	52.0MHz	-30 to 85	$\pm$ 0.5	2	-	-

*This document was correct at the time of printing; please contact your local sales office for the latest version.*

[Click to view latest version on our website.](#)

#### Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1 760 668 8935

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)

Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)